PowerXtreme X10

ower

Battery 12 V 10 Ah



EARS NARRANTY

* After registration

LiFePO4: the safest lithium technology Very low self-discharge, low maintenance & safe



Extreme power 100 A continuous - 200 A peak

Sustainable

More than 2000 cycles - completely recyclable

Lightweight and small

Only 2.1 kg - 182x120x90 mm - for caravans up to 1500 kg



Smart Bluetooth BMS & app Wireless information on your smart device including on/off function



Simple installation Including pole set, practical mounting bracket and supplied charger

reme





| Technical specifications | |
|-------------------------------|---------------------------------------------------------------------------------------|
| Model | X10 |
| Article number | EM010046EN |
| Cell chemistry | LiFePO4 (Lithium Iron Phosphate) |
| Lifetime | > 2000 cycles (80% DOD) |
| Warranty | 5 years (2 years standard + 3 years extra after registration) and maximum 2000 cycles |
| Housing | PC / ABS |
| Connection | M6 internal thread + 2 separate battery poles |
| IP class | IP 62 |
| Storage temperature | -10°C to +45°C |
| Communication | Bluetooth (readable via PowerXtreme App) |
| Utilization | Caravan mover |
| Output (discharge) | |
| Nominal voltage | 12.8 V |
| Capacity | 10 Ah / 128 Wh |
| Nominal continuous current | 100 A / 1200 W |
| Short-term current (≤ 30 sec) | 150 A / 1800 W |
| Peak current (≤ 3 sec) | 200 A / 2400 W |
| Operating temperature | -20°C to +60°C |
| Maximum discharge voltage | ≤ 10,5 V |
| Input (charge) | |
| Maximum charging voltage | 14.6 V |
| Maximum charging current | 10 A (via battery terminals) |
| Charge temperature | 0°C to +45°C |
| Included charger | 14.6 V / 2 A |
| AC input charger | 100 - 240 VAC |
| Dimensions | |
| Length | 182 mm |
| Width | 120 mm |
| Height | 90 mm |
| Weight | 2.1 kg |
| Safety / Certification | |
| Security | Overcurrent / over- and undervoltage / short circuit / temperature |
| Compliance | UN38.3 / MSDS / CE |

